



Tolerancje wg ISO dla wałów i otworów

Średnica znamionowa wału (mm)		d 11		e 8		e 7		f 8		f 7		g 6		h 11		h 9		h 8		h 7	
od	do	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną
3	6	-30	-105	-20	-38	-20	-32	-10	-28	-10	-22	-4	-12	0	-75	0	-30	0	-18	0	-12
6	10	-40	-130	-25	-47	-25	-40	-13	-35	-13	-28	-5	-14	0	-90	0	-36	0	-22	0	-15
10	18	-50	-160	-32	-59	-32	-50	-16	-43	-16	-34	-6	-17	0	-110	0	-43	0	-27	0	-18
18	30	-65	-195	-40	-73	-40	-61	-20	-53	-20	-41	-7	-20	0	-130	0	-52	0	-33	0	-21
30	50	-80	-240	-50	-89	-50	-75	-25	-64	-25	-50	-9	-25	0	-160	0	-62	0	-39	0	-25
50	80	-100	-290	-60	-106	-60	-90	-30	-76	-30	-60	-10	-29	0	-190	0	-74	0	-46	0	-30
80	120	-120	-340	-72	-126	-72	-107	-36	-90	-36	-71	-12	-34	0	-220	0	-87	0	-54	0	-35
120	180	-145	-395	-85	-148	-85	-125	-43	-106	-43	-83	-14	-39	0	-250	0	-100	0	-63	0	-40
180	250	-170	-460	-100	-172	-100	-146	-50	-122	-50	-96	-15	-44	0	-290	0	-115	0	-72	0	-46
250	315	-190	-510	-110	-191	-110	-162	-56	-137	-56	-108	-17	-49	0	-320	0	-130	0	-81	0	-52
315	400	-210	-570	-125	-214	-125	-182	-62	-151	-62	-119	-18	-54	0	-360	0	-140	0	-89	0	-57
400	500	-230	-630	-135	-232	-135	-198	-68	-165	-68	-131	-20	-60	0	-400	0	-155	0	-97	0	-63

Średnica znamionowa wału (mm)		h 6		h 5		j 6		k 6		k 5		m 6		m 5		n 6		p 6	
od	do	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną
3	6	0	-8	0	-5	+7	-1	-	-	-	-	+12	+4	+9	+4	+16	+8	+20	+12
6	10	0	-9	0	-6	+7	-2	+10	+1	+7	+1	+15	+6	+12	+6	+19	+10	+24	+15
10	18	0	-1	0	-8	+8	-3	+12	+1	+9	+1	+18	+7	+15	+7	+23	+12	+29	+18
18	30	0	-3	0	-9	+9	-4	+15	+2	+11	+2	+21	+8	+17	+8	+28	+15	+35	+22
30	50	0	-16	0	-11	+11	-5	+18	+2	+13	+2	+25	+9	+20	+9	+33	+17	+42	+26
50	80	0	-19	0	-13	+12	-7	+21	+2	+15	+2	+30	+11	+24	+11	+39	+20	+51	+32
80	120	0	-22	0	-15	+13	-9	+25	+3	+18	+3	+35	+13	+28	+13	+45	+23	+59	+37
120	180	0	-25	0	-18	+14	-11	+28	+3	+21	+3	+40	+15	+33	+15	+52	+27	+68	+43
180	250	0	-29	0	-20	+16	-13	+33	+4	+24	+4	+46	+17	+37	+17	+60	+31	+79	+50
250	315	0	-32	0	-23	+16	-16	+36	+4	+27	+4	+52	+20	+43	+20	+66	+34	+88	+56
315	400	0	-36	0	-25	+18	-18	+40	+4	+29	+4	+57	+21	+46	+21	+73	+37	+98	+62
400	500	0	-40	0	-27	+20	-20	+45	+5	+32	+5	+63	+23	+50	+23	+80	+40	+108	+68

Średnica znamionowa otworu (mm)		D 11		E 8		E 7		F 8		F 7		G 6		G 11		H 9		H 8		H 7	
od	do	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną
3	6	+105	+30	+38	+20	+32	+20	+28	+10	+22	+10	+16	+4	+75	0	+30	0	+18	0	+12	0
6	10	+130	+40	+47	+25	+40	+25	+35	+13	+28	+13	+20	+5	+90	0	+36	0	+22	0	+15	0
10	18	+160	+50	+59	+32	+50	+32	+43	+16	+34	+16	+24	+6	+110	0	+43	0	+27	0	+18	0
18	30	+195	+65	+73	+40	+61	+40	+53	+20	+41	+20	+28	+7	+130	0	+52	0	+33	0	+21	0
30	50	+240	+80	+89	+50	+75	+50	+64	+25	+50	+25	+34	+9	+160	0	+62	0	+39	0	+25	0
50	80	+290	+100	+106	+60	+90	+60	+76	+30	+60	+30	+40	+10	+190	0	+74	0	+46	0	+30	0
80	120	+340	+120	+126	+72	+107	+72	+90	+36	+71	+36	+47	+12	+220	0	+87	0	+54	0	+35	0
120	180	+395	+145	+148	+85	+125	+85	+106	+43	+83	+43	+54	+14	+250	0	+100	0	+63	0	+40	0
180	250	+460	+170	+172	+100	+146	+100	+122	+50	+96	+50	+61	+15	+290	0	+115	0	+72	0	+46	0
250	315	+510	+190	+191	+110	+162	+110	+137	+56	+108	+56	+69	+17	+320	0	+130	0	+81	0	+52	0
315	400	+570	+210	+214	+125	+182	+125	+151	+62	+119	+62	+75	+18	+360	0	+140	0	+89	0	+57	0
400	500	+630	+230	+232	+135	+198	+135	+165	+68	+131	+68	+83	+20	+400	0	+155	0	+97	0	+63	0

Średnica znamionowa otworu (mm)		H 6		J 7		J 6		K 7		K 6		M 7		M 6		N 7		N 6		P 7	
od	do	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną	górną	dolną
3	6	+8	0	+5	-7	+4	-4	-	-	-	-	0	-12	-1	-9	-4	-16	-5	-13	-8	-20
6	10	+9	0	+8	-7	+5	-4	+5	-10	+2	-7	0	-15	-3	-12	-4	-19	-7	-16	-9	-24
10	18	+11	0	+10	-8	+6	-5	+6	-12	+2	-9	0	-18	-4	-15	-5	-23	-9	-20	-11	-29
18	30	+13	0	+12	-9	+8	-5	+6	-15	+2	-11	0	-21	-4	-17	-7	-28	-11	-24	-14	-35
30	50	+16	0	+14	-11	+10	-6	+7	-18	+3	-13	0	-25	-4	-20	-8	-33	-12	-28	-17	-42
50	80	+19	0	+18	-12	+13	-6	+9	-21	+4	-15	0	-30	-5	-24	-9	-39	-14	-33	-21	-51
80	120	+22	0	+22	-13	+16	-6	+10	-25	+4	-18	0	-35	-6	-28	-10	-45	-16	-38	-24	-59
120	180	+25	0	+26	-14	+18	-7	+12	-28	+4	-21	0	-40	-8	-33	-12	-52	-20	-45	-28	-68
180	250	+29	0	+30	-16	+22	-7	+13	-33	+5	-24	0	-46	-8	-37	-14	-60	-22	-51	-33	-79
250	315	+32	0	+36	-16	+25	-7	+16	-36	+5	-27	0	-52	-9	-41	-14	-66	-25	-57	-36	-88
315	400	+36	0	+39	-18	+29	-7	+17	-40	+7	-29	0	-57	-10	-46	-16	-73	-26	-62	-41	-98
400	500	+40	0	+43	-20	+33	-7	+18	-45	+8	-32	0	-63	-10	-50	-17	-80	-27	-67	-45	-108

Wszystkie wymiary podano w µm

Uwagi ogólne:

Wszystkie informacje techniczne i porady oparte są o dotychczasowe doświadczenia producenta.

W1-11/2007

PIERŚCIENIE ZACISKOWE